

# Penguard EXPRESS

CORROSION PROTECTION WITH SPEED, COLOUR AND EFFICIENCY



# Penguard express

# Tailor corrosion protection to fit your needs!



# **SPEED**

- Very fast dry-to-recoat
- Very fast dry-to-handle
- Fast drying in temperatures from -5°C to 40°C
- Full system completion within one day even at low temperatures



# **COLOUR**

- For areas where exact colour match and colour stability matter, Penguard Express CF offers the following benefits:
  - Jotun Multicolour Industry tinting system gives virtually unlimited colour choice
  - Less yellowing and darkening
  - Better performance in touch up and repair work at the new construction site



# **EFFICIENCY**

- Fast hardness development minimises damage when structures are moved and stacked
- Fast curing reduces the need for space for drying painted structures
- Low temperature cure extends production periods and also allows application in cold climates
- Extended production periods reduce heating costs, risk of errors and simplify application
- High volume solids reduces paint volume required



# **Penguard** express

Penguard Express is a fast drying, high solids 2-pack epoxy coating which may be applied in high film thickness and at lower temperatures. For use as an anti-corrosive primer or intermediate coat for the protection of steel and other substrates in atmospheric exposure. The fast dry-to-recoat and dry-to-handle times allow for increased throughput and efficiency during the paint application process. Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

# Penguard EXPRESS ZP

Penguard Express ZP is pigmented with active zinc phosphate for increased corrosion protection and is the natural choice as a first coat for protection of metal structures exposed in highly corrosive environments. Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

# **Penguard** EXPRESS MIO

Penguard Express MIO is reinforced with micaceous iron oxide pigments for increased barrier effect. This effect is provided by overlapping layers of the MIO pigments which prevent moisture penetrating through the paint film.

It further provides increased hardness and improved adhesion of subsequent coats.

Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

# **Penguard** EXPRESS CF

Penguard Express CF, the most recent addition to the Penguard Express range, offers more colour stability and a wide range of colours through MCI. It offers all the benefits of Penguard Express and can be delivered in small batches.




# Penguard express

# The ideal solution for all steel substrates

# **Exposed Steel Structures**

Steel structures which are exposed to tough atmospheric environments, need a coating system that provides long term, durable protection.



Typically the coating system can be based on a zinc rich primer, 1 or 2 coats of high build epoxy with a topcoat. Penguard Express will provide strong adhesion to both the zinc primer and the topcoat giving excellent protection.

By using Penguard Express it is possible to apply even a 3 coat system in one day. At 10°C this can be completed within 10 hours. In warmer climates where the steel substrate may reach 40°C, it can even be completed in less than 3 hours.

### **Structural Steelwork**

Structural steel for infrastructure projects is usually protected with one or two coats of an epoxy eventually with a topcoat.

Application of a 2 coat Penguard Express coating system can be completed within 8 hours at 10°C or within just 2 hours should the temperature reach 40°C.



## Where colour and colour stability matter

Penguard Express CF meets our customers' needs for a fast curing epoxy coating that is available in a wide range of colours.

Penguard Express CF meets the demands for a more colour stable epoxy coating combined with excellent anticorrosive properties.

Penguard Express CF can be used direct to steel and in one coat application.



# Product data

|                                   | Penguard<br>Express                             | Penguard<br>Express ZP | Penguard<br>Express MIO   |                | juard<br>ess CF           |
|-----------------------------------|---|------------------------|---------------------------|----------------|---------------------------|
| Dry film thickness µm (min – max) | 75 – 250  | 75 – 250               | 75 – 250                  | 100 -          | - 250                     |
| Solids (vol%)                     | 74 ± 2  | 74 ± 2                 | 74 ± 2                    | 77             | ± 2                       |
| VOC g/I (EPA Method 24)           | 260   | 260                    | 260                       | 23             | 31                        |
| Pot life                          | 2 hr  | 2 hr                   | 2 hr                      | 1 hr           |                           |
| Colours                           | Grey, Grey XO, Red,<br>Buff, Light Red          | Grey, Red              | Grey, Red                 |                | oice with<br>ng system    |
| Mixing ratio                      | 4 parts Comp. A (base)                          |                        |                           | •••••          |                           |
|                                   | 1 part Comp. B (curing agent)                   |                        |                           |                |                           |
| Pot life (23°C)                   | 2 hours 1 ho<br>(reduced at higher temperature) |                        | our                       |                |                           |
| Drying times                      | Surface<br>Dry                                  |                        | Dry to<br>recoat<br>(min) | Surface<br>Dry | Dry to<br>recoat<br>(min) |
| 40°C                              | 0.5 hr  |                        | 1 hr                      | 1 hr           | 1.5 hrs                   |
| 23°C                              | 1 hr  |                        | 2 hrs                     | 2.5 hrs        | 3 hrs                     |
| 10°C                              | 2 hrs   |                        | 4 hrs                     | 4.5 hrs        | 6 hrs                     |
| 0°C                               | 11 hrs  |                        | 14 hrs                    | 16 hrs         | 24 hrs                    |
| -5°C                              | 16 hrs  |                        | 24 hrs                    | -              | _                         |

# Typical systems

There are many factors influencing the choice of coatings for protection of a steel structure. Penguard range of products can be applied in a wide range of situations.

Any Penguard Express variant can be used in the system examples shown.

Used in combination with zinc rich primers, the service life of the coating system will be prolonged in higher corrosive areas.

In UV exposed areas and where long colour and gloss durability are required, a high performance topcoat should be used.

# ONE COAT APPLICATION FOR LOWER CORROSIVE AREAS

| Product          | Coats | DFT μm |
|------------------|-------|--------|
| Penguard Express | 1     | 80*    |

# SYSTEMS FOR MEDIUM CORROSIVE AREAS

| Product          | Coats | DFT μm |
|------------------|-------|--------|
| Penguard Express | 1     | 175    |

| Product          | Coats | DFT μm |
|------------------|-------|--------|
| Penguard Express | 1     | 80*    |
| Penguard Express | 1     | 80*    |

### TWO OR THREE COAT SYSTEMS FOR HIGH AND VERY HIGH CORROSIVE AREAS

| Product          | Coats | DFT μm |
|------------------|-------|--------|
| Penguard Express | 1     | 160    |
| Penguard Express | 1     | 160    |

| Product          | Coats | DFT μm |
|------------------|-------|--------|
| Barrier 80       | 1     | 60     |
| Penguard Express | 1     | 100    |
| Penguard Express | 1     | 100    |

<sup>\*</sup>Penguard Express CF: Min. 100 μm DFT





# Delivering speed, colour and efficiency to the production process

Reduced recoating times and shorter dry-to-handle periods save time, lower costs and increase output

- Speeds up the production process and improves efficiency for applicators, contractors and steel fabricators
- Saves heating costs
- Reduces risk of errors and simplifies application by using same curing agent at low and high temperatures
- Easy to apply. Can also be applied by brush and roller
- Save coats and processing times by using any Penguard Express variant as single coat, primer or intermediate coat

# Penguard Express CF provides wider choice of colours and better colour stability

- More colour stable than other fast curing epoxy primers especially in non-UV exposed areas
- Can be applied directly to metal or as part of a system
- Provides all the benefits of Penguard Express and can be delivered fast and in small batches anywhere
- Provides fast handling, simplifies logistics and improves performance in touch up and repair work at the new construction site



# A global provider of coatings



Jotun is one of the world's leading manufacturers of paints, coatings and powder coatings.

We have 68 companies in 43 countries and 33 production facilities in 20 countries on all continents, and are represented in more than 90 countries with our network of agents, branch offices, distributors and sales offices around the world.

Our operations cover development, production, marketing, R&D and sales of paints and coatings to protect and decorate surfaces in residential, shipping and industrial markets.

# UNIFORM STANDARD ACROSS THE GLOBE



- Easy to exchange trained technical personnel across national borders and multinational projects.
- Compulsory training for all technical and sales personnel in marine and protective segments.
   Most of our coating advisors and technical personnel have FROSIO and/or NACE certification.
- Same competence in maintaining company standard procedures globally.

# Jotun GreenSteps =

# FOR A MORE COLOURFUL WORLD, WE ALL NEED TO BE A LITTLE GREENER

Jotun recognises the responsibility it has to the environment and has established its own GreenSteps programme.

Through the GreenSteps programme we address market demand for more sustainable coatings solutions.











# Jotun Marine Coatings and Jotun Protective Coatings offices worldwide

Legal Jotun entities worldwide are listed. For details of Branch offices and Jotun representation in countries not listed. please visit **jotun.com** 

#### AUSTRALIA

Jotun Australia Pty. Ltd., P.O. Box 105, Altona North, 9 Cawley Road, BROOKLYN, VIC 3025 Tel: +61 3 9314 0722 Fax: +61 3 9314 0423

#### RRA7II

Jotun Brasil Ltda. Estrada Ademar Ferreira Torres 250 Caluge - Itaborai (RJ) CEP 24808-520 RIO DE JANEIRO Tel: +55 21 3147 3850 Fax: +55 21 3147 3861

#### **CYPRUS**

Jotun Cyprus Ltd.
56 Theodorou Potamianou
Aphrodite Court, 1st Floor
4155, Kato Polemidia
LIMASSOL
Tel: +357 25 374455 / 374440 / 374477
Fax: +357 25 374400

#### P.R. of CHINA

Jotun Coatings (Zhangjiagang) Co. Ltd. Jotun COSCO Marine Coatings (Qingdao) Co. Ltd. Floor 20, Jiu Shi Mansions, No. 28 Zhong Shan Road (South) SHANGHAI 200010 Tel: +86 21 6333 080 0 Fax:+86 21 6326 968 6

Jotun Coatings (Zhangjiagang) Co. Ltd. Jotun COSCO Marine Coatings (Qingdao) Co. Ltd. Room 709-12, Goldlion Digital Network Centre, 138 Tiyu Road East, GUANGZHOU, 510620 Tel: +86 20 38 78 07 49 Fax:+86 20 38 78 19 66

HONG KONG Jotun COSCO Marine Coatings (H.K.) Ltd Room 902, 9/F, 101 King's Road, North Point HONG KONG Tel: +852 2527 6466 Fax:+852 2861 1307

## DENMARK

Jotun Danmark A/S Jotun Coatings Columbusvej 5, 2860 Søborg, COPENHAGEN Tel: +45 4492 9400 Fax:+45 4492 9401

### **EGYPT**

El Mohandes Jotun S.A.E. Plot 193, Second District, City Center, Fifth Settlement, NEW CAIRO Tel: +202 2614 9999 Fax: +202 2614 9998

### **FINLAND**

Nor-Maali OY Vanhatie 20, 15240 LAHTI Tel: +358 3 874 650 Fax:+358 3 874 6550

### FRANCE

Jotun France S.A. 22/24 Rue du President Wilson, Bat.A 92300 LEVALLOIS PERRET Tel: +33 1 4519 3882 Fax:+33 1 4519 3894

#### GERMAN

Jotun (Deutschland) GmbH Haferweg 38 22769 HAMBURG Tel: +49 40 851 960 Fax:+49 40 856 234

#### **GREAT BRITAIN**

Jotun Paints (Europe) Ltd. Stather Road, Flixborough, SCUNTHORPE DN15 8RR Tel: +44 1724 400 000 Fax:+44 1724 400 100

#### GREECE

Jotun Hellas Ltd.

33, Zeppou Street, Glyfada ATHENS 16675 Tel: +30 210 42 85 980-82 +30 210 42 86 035-37 Fax:+30 210 42 85 983/ +30 210 42 87 237

#### INDIA

Jotun India Pvt Ltd.
502, 5th Floor,
Boston House,
Suren Road,
Behind Cinemax Theatre,
Andheri East,
Mumbai – 400 093
Tel: +91 22 2822 4600
+91 22 2820 5900 (+fax)
Fax:+91 22 2820 5900

#### INDONESIA

P.T. Jotun Indonesia Kawasan Industri MM2100 Blok KK-1, Cikarang Barat Bekasi 17520 Tel: +62 21 8998 2657 Fax:+62 21 8998 2658

### IRELAND

Jotun (Ireland) Ltd., Unit K7, Marina Commercial Park, Centre Park Road, CORK Tel: +353 214 965955 Fax:+353 214 965992

### ITALY

Jotun Italia S.P.A. Via Petronio, 8, Zona Ind. Noghere 34147 - MUGGIA (TRIESTE) Tel: +39 040 23 98204 Fax:+39 040 23 98222

### JAPAN

NKM Coatings Co., Ltd. 12–1, Minamirokugo 3-chome, Ota-ku, TOKYO 144-0045 Tel: +81 3 6758 2212 Fax:+81 3 6758 2213

### **KOREA (SOUTH)**

Chokwang-Jotun Ltd. 30th Block Jisa Science Park, 1205 Jisa-dong, Gangseo-gu, BUSAN 618-230 Tel: +82 517 976 000 Fax:+82 517 117 735

### LIBYA

Jotun Libya J.S.Co Almumtaz Co. S.A. (Jotun). Alseka Street P.O. Box 6850 TRIPOLI Tel:+218 214777811 Fax:+218 214780718

#### MALAYSIA

Jotun Paints (Malaysia) Sdn. Bhd. Lot 7 Persiaran Perusahaan, Section 23, Po. Box 7050 40700 SHAH ALAM Tel: +60 351 235 500 Fax:+60 351 235 632

## THE NETHERLANDS

Jotun B.V.
Postbus 208
3200 AE SPIJKENISSE
Visiting address:
Curieweg 11b, 3208 KJ Spijkenisse
ROTTERDAM
Tel: +31 181 678 300
Fax:+31 181 617 899

# NORWAY

P.O. Box 2021, 3202 SANDEFJORD Visiting address: Hystadveien 167, 3209 Sandefjord Tel: +47 33 45 70 00 Fax:+47 33 45 79 00

#### OMAN

Jotun Paints Co. LLC Rusayl Ind. Estate, Road No.10 P.O. Box 672 Code 111, MUSCAT Tel: +968 2444 6100 Fax:+968 2444 6105

#### PAKISTA

Jotun Pakistan (Pvt.) Ltd. 2KM Defence Road, Off 9KM Raiwind Road, Adjacent Valencia Homes Gate LAHORE 544770 Tel: +92 423 532 350 0-3 Fax:+92 423 532 1387

#### **PHILIPPINES**

Jotun (Philippines) Inc. 846 West Service Road, Km.18 South Super Highway Paranaque City, METRO MANILA 1714 Tel: +63 2239 1032-34 Fax:+63 2822 0760

### **POLAND**

Jotun Polska Sp.zo.o. ul. Magnacka 15, 80-180 GDAŃSK KOWALE Tel: +48 58 555 1515 Fax:+48 58 781 9692

### RUSSIA

Jotun Paints O.O.O. Varshavskaya Str., 23/2, Office 75 196128 ST. PETERSBURG Tel: +7 812 640 00 80 Fax:+7 812 640 00 81

## SAUDI ARABIA

Jotun Saudia Co. Ltd. Jeddah Industrial City, Phase 3, P.O. Box 34698, JEDDAH 21478 Tel: +966 2635 0535 / 2636 1271 Fax:+966 2636 2483

### SINGAPORE

Jotun (Singapore) Pte. Ltd. 37 Tuas View Crescent Singapore 637236 Tel: +65 650 882 88 Fax:+65 6265 7484

### SOUTH AFRICA

Jotun Paints South Africa (PTY) Ltd. Wimbledon Road, P.O.Box 187 BLACKHEATH 7581 Tel: +27 21 905 1070 Fax:+27 21 905 1652

### SPAIN

Jotun Iberica S.A. Poligon Santa Rita, Calle Estatica no. 3, 08755 Castellbisbal, BARCELONA Tel: +34 937 711 800 Fax:+34 937 711 801

#### **SWEDEN**

Jotun Sverige AB P.O. Box 151, Klangfärgsgatan 13, 421 22 VÄSTRA FRÖLUNDA Tel: +46 3169 6300 Fax:+46 3169 6397

### THAILAND

Jotun Thailand Ltd Amata Nakom Ind. Estate (BIPII) 700/353 Moo 6 Tumbol Donhualoh, Amphur Muang CHONBURI 2000 Tel: +66 2 022 9888 Fax:+66 38 214 373/375

#### **TURKEY**

Jotun Boya San. ve Ticaret. A.S. Balabandere Caddesi Hilpark Suites Sitesi No.10, Istinye 34460 Sariyer ISTANBUL Tel: +90 21 2279 7878 Fax:+90 21 2279 2549

### U. A. E.

Abu Dhabi Jotun Abu Dhabi (LLC) P.O. Box 3714, Mussafah ABU DHABI Tel: +971 2691 0700 Fax:+971 2551 0232

Dubai Jotun U.A.E. Ltd. (LLC) P.O. Box 3671, Al Quoz Industrial Area DUBAI Tel: +971 4339 5000 Fax:+971 4338 0666

### USA

Jotun Paints Inc. 9203 Highway 23, P.O. Box 159, Belle Chasse, LA 70037 Tel: + 1 713 860 8241 Fax: +1 713 860 8242

# VIETNAM

Jotun Paints (Vietnam) Co. Ltd. Song Than Industrial. Zone, No.1 Street 10, Di An District, Binh Duong Province Tel: +84 650 3742206 Fax:+84 650 374 2205

### YEMEN

Jotun Yemen Paints Co. Ltd P.O. Box 70183, Al Alam ADEN Tel: +967 2820 546-9 Fax:+967 2249 362

